

COUNTER

STW-C
PC
BC

THUMBWHEEL COUNTER



STW - 721C

PRESET COUNTER



PC-961

BATCH COUNTER



BC-961

Case Size	96 x 96 x 45	72 x 72 x 65	96 x 96 x 45	72 x 72 x 65	48 x 48 x 75
Panel Hole Size	92 x 92	67 x 67	92 x 92	67 x 67	46 x 46
Range Limit	0-99999 Count		0-9999 Count		0-999999 Count
Input	NPN/ PNP Proximity, Potential Free Contact, Photocell				
Sensor Supply	12 VDC / 30 mA				
Input Speed	0 - 10 KHz				0 - 10 KHz
Accuracy	$\pm$ 1 Count		$\pm$ 1 Count		$\pm$ 1 RPM
Function	3/4/5 Digit Counter		4 Digit Counter		6 Digit Counter / 4 Digit RPM
Output	1 Relay / Buzzer - NO/ NC (230 VAC / 5 AMP), Buzzer - 12 VDC, 10 mA				
Counting	Up		Up / Down		Up
Display	Single Display		4 Digit Dual Display		6 Digit Upper / 4 Digit Lower Display
Keyboard	Thumbwheel Setting		4 Keys		
Reset	Auto / Manual - Front / Back Reset				
Memory	Yes (Non-Volatile Memory)				
Front Protection	ABS Plastic Body				
Mounting	Flush Panel Mounting With Side Clamp				
Power Supply	230 VAC $\pm$ 10%, 50 HZ		90-270 VAC, 50 HZ		230 VAC $\pm$ 10%, 50 HZ
Envirnment	Temp : 0 - 50°C / Rh : 35 - 85 % (Non - Condensation)				

LC
TBC
SMC



LENGTH COUNTER



TABLET COUNTER



CLUTCH & BREAK CONTROLLER

Case Size	96 x 96 x 45	72 x 72 x 65	48 x 48 x 75	96 x 96 x 90	96 x 96 x 45
Panel Hole Size	92 x 92	67 x 67	46 x 46	92 x 92	92 x 92
Range Limit	0-99999.9 Meter			0-99999999 Tablet	0-999999 Count
Input	NPN/ PNP Proximity, Potential Free Contact, Photosell				Proximity, Color mark Sensor
Sensor Supply	12 VDC / 30 mA				
Input Speed	10 KHz				
Accuracy	± 1 Count				
Function	Diameter / PPR Setting		Total Table, selectable Station / Rotor Parameter		Clutch / Brake
Output	1 Relay				2 Relay (Motor / Cutter)
Relay	230 VAC / 5 AMP				
Counting	Up				
Display	6 Digit Upper / 4 Digit Lower Display		8 Digit Upper / 4 Digit Lower Display		6 Digit Upper / 4 Digit Lower Display
	6 Digit Total Length / 4 Digit MPM		8 Digit Total Tablet / 4 Digit TPM		6 Digit Total Count / 4 Digit Time
Keyboard	4 Keys				
Reset	Auto / Manual - Front / Back Reset				
Memory	Yes (Non-Volatile Memory)				
Front Protection	ABS Plastic Body				
Mounting	Flush Panel Mounting With Side Clamp				
Power Supply	230 VAC± 10%, 50 HZ				
Enviornment	Temp : 0 - 50°C / Rh : 35 - 85 % (Non - Condensation)				