


TIMER

THUMBWHEEL TIMER

STW
STW-N
STW-U



STW - 961



STW - 961-N



STW - 721-U

Case Size	96 x 96 x 65	72 x 72 x 80	96 x 96 x 50	72 x 72 x 75	96 x 96 x 50	72 x 72 x 75	48 x 48 x 90
Panel Hole Size	92 x 92	67 x 67	92 x 92	67 x 67	92 x 92	67 x 67	46 x 46
Range Limit	99.9 / 999				9.99 / 99.9 / 999		
Unit	Sec. / Min				Sec. / Min. / Hr.		
Mode	On Delay				On / Off Delay		
Set Point	1 Set Point						
Output	1 Relay (2 C/O)						
Description	Relay (5 Amp / 230 VAC)						
Display / color	3 Digit Single Display (0.56" Red)						
Keyboard	Thumbwheel Setting						
Start Input	Power On Start				Potential Free Contact / Power On Start		
Indication	Indication For Relay Status						
Reset	Front Reset				Front / Back Reset		
Counting	Up				Up / Down Programable		
Memory	NO				Selectable Memory option		
Front Protection	Metal Body		ABS Plastic Body				
Mounting	Panel Mounting with side Clamp						
Power Supply	230 VAC, $\pm$ 10 %, 50 Hz						
Envirnment	Temp : 0 - 50°C / Rh : 35 - 85 % (Non - Condensation)						

UT
SST

UNIVERSAL TIMER



UT-7221



UT-481



SEQUENTIAL TIMER

SST-968

Case Size	96 x 96 x 50	72 x 72 x 45	48 x 48 x 90	48 x 48 x 75	96 x 96 x 85
Panel Hole Size	92 x 92	67 x 67	46 x 46	46 x 46	92 x 92
Range Limit	9.999 / 99.99 / 999.9 / 9999			9.99 / 99.9 / 999	9.999 / 99.99 / 999.9 / 9999
	99.59 Min - Sec. 99.59 Hr. - Min.				
Unit	Sec./ Min./ Hr.			Sec./ Min./ Hr.	Sec./ Min./ Hr.
Mode	On Delay / Preset / Cyclic / Laundry			On Delay / Preset / Cyclic	Cycle / Delay time for each step - Common
					Selection for Skipping stage
Set Point	2 Set Point				4 / 8 Set Point
Output	2 Relay (1 C/O)			1 Relay (1 C/O)	4 / 8 Relay (1 C/O)
Description				Relay (5 Amp / 230 VAC)	
Display	4 Digit Dual Display			3 Digit Single Display	4 Digit Dual Display
Color	Red - Upper / Green - Lower			Red	Red - Upper / Green - Lower
Keyboard	Feather Touch Key Board				
Start Input	Proximity / Potential Free Contact / Power On Start				
Indication	Indication For Relay Status				
Function	Front / Back Reset / Up - Down Count / Memory Selection (Yes/No)				
Front Protection	ABS Plastic Body				
Mounting	Panel Mounting with side Clamp				
Power Supply	90 - 270 VAC, 50 Hz				
Envirnment	Temp : 0 - 50°C / Rh : 35 - 85 % (Non - Condensation)				